

BS-2700 LIQUID NAILS

Page: 1

Compilation date: 16/03/2018

Revision No: 0

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BS-2700 LIQUID NAILS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name:	Bossil Technology Sdn. Bhd.	
	Lot 165, Jalan Industri 1/2,	
	Rawang Integrated Industrial Park,	
	Rawang,	
	Selangor,	
	48000	
	Malaysia.	
Tel:	+6016-2119190	
Email:	sales@bossil.com	

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substa	nce or mixture
Classification under CLP:	Flam. Liq. 2: H225; Aquatic Chronic 3: H412; Repr. 2: H361f; Skin Irrit. 2: H315; STOT RE
	2: H373; STOT SE 3: H336; -: EUH208
Most important adverse effects:	Contains octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine. May
	produce an allergic reaction. Highly flammable liquid and vapour. Causes skin irritation.
	May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage
	to organs through prolonged or repeated exposure. Harmful to aquatic life with long
	lasting effects.
2.2. Label elements	
Label elements:	
Hazard statements:	EUH208: Contains octadecanoic acid, 12-hydroxy-, reaction products with
	ethylenediamine. May produce an allergic reaction.
	H225: Highly flammable liquid and vapour.
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.

H361f: Suspected of damaging fertility.

[cont...]

BS-2700 LIQUID NAILS

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



Signal words: Danger

eigna noraei	Dangor
Precautionary statements:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P241: Use explosion-proof electrical/ventilating/lighting/ equipment.
	P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352: IF ON SKIN: Wash with plenty of water.
	P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

KAOLIN

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	1332-58-7	Substance with a Community workplace exposure limit.	-	10-30%

N-HEXANE

203-777-6	110-54-3	-	Flam. Liq. 2: H225; Repr. 2: H361f;	10-30%
			Asp. Tox. 1: H304; STOT RE 2: H373;	
			Skin Irrit. 2: H315; STOT SE 3: H336;	
			Aquatic Chronic 2: H411	

LIMESTONE

215-279-6	1317-65-3	Substance with a Community workplace exposure limit.	-	10-30%
OCTADECANOIO	CACID, 12-HYDR	OXY-, REACTION PRODUCTS WITH ET	THYLENEDIAMINE	
309-629-8	100545-48-0	-	Skin Sens. 1B: H317	<1%

Section 4: First aid measures

Page: 2

BS-2700 LIQUID NAILS

		Page:	
4.1. Description of first aid mea	sures		
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash		
	immediately with plenty of soap and water.		
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
Ingestion:	Ingestion: Wash out mouth with water. Consult a doctor.		
Inhalation:	Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a		
	doctor.		
4.2. Most important symptoms a	and effects, both acute and delayed		
Skin contact:	There may be irritation and redness at the site of contact.		
Eye contact:	There may be irritation and redness. The eyes may water profusely.		
Ingestion:	There may be soreness and redness of the mouth and throat.		
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may		
	cause coughing or wheezing.		
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.		
4.3. Indication of any immediate	medical attention and special treatment needed		
Immediate / special treatment:	Eye bathing equipment should be available on the premises.		
ection 5: Fire-fighting measur	es		
5.1. Extinguishing media			
Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used. Use water spray		
	to cool containers.		
5.2. Special hazards arising from	n the substance or mixture		
<u>_</u>	In combustion emits toxic fumes.		
5.3. Advice for fire-fighters			
Advice for fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact		
	with skin and eyes.		
ection 6: Accidental release m	easures		
6.1. Personal precautions, prote	ective equipment and emergency procedures		
Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from		
	downwind. If outside keep bystanders upwind and away from danger point. Mark out the		
	contaminated area with signs and prevent access to unauthorised personnel. Turn		
	leaking containers leak-side up to prevent the escape of liquid.		
6.2. Environmental precautions			

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

BS-2700 LIQUID NAILS

Page: 4

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

KAOLIN

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	2 mg/m³	-

Respirable dust

N-HEXANE

UK	72 mg/m3	-	_	-
LIMESTONE				
UK	10 mg/m³	-	4 mg/m³	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

BS-2700 LIQUID NAILS

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties		
State:	Liquid	
Colour:	Brown	
Odour:	Characteristic odour	
Evaporation rate:	Not applicable.	

	Not applicable.		
Oxidising:	Not classified as oxidising		
Solubility in water:	Not determined		
Boiling point/range°C:	>35	Flash point°C:	<23
Vapour pressure:	Not applicable.	Relative density:	Approximately 1.16
pH:	Not applicable.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

BS-2700 LIQUID NAILS

Hazardous ingredients:

KAOLIN

ORAL RAT LD50	5000	mg/kg	
---------------	------	-------	--

N-HEXANE

IPR	RAT	LDLO	9100	mg/kg
IVN	MUS	LDLO	831	mg/kg
ORL	RAT	LD50	25	gm/kg

LIMESTONE

ORAL RAT LD50	2000	mg/kg
---------------	------	-------

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Reproductive toxicity		Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

LIMESTONE

Daphnia magna	48H EC50	100	mg/l
FISH	96H LC50	100	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	14	mg/l

Page: 6

BS-2700 LIQUID NAILS

Page: 7

OCTADECANOIC ACID, 12-HYDROXY-, REACTION PRODUCTS WITH ETHYLENEDIAMINE

Daphnia magna	48H EC50	10	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	100	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	10	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

BS-2700 LIQUID NAILS

Page: 8

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information	
Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction.</name>
	H225: Highly flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H336: May cause drowsiness or dizziness.
	H361f: Suspected of damaging fertility.
	H373: May cause damage to organs through prolonged or repeated exposure.
	H411: Toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.