

Safety Data Sheet

BS-3100 Vinyl Adhesive

Telephone

: +6016 - 2119190

Issued date: 23/12/16 Revision date: 06/06/18 Revision No.: 1

1. Identification of the substance/preparation and of the company/undertaking

Product name: BS-3100 Vinyl Adhesive Product use : Water-based adhesive Company

: Bossil Technology Sdn. Bhd.

22A-1, Jalan Tasik Utama 10, Fax

The Trillium @ Lake Fields, : sales@bossil.com **Email** Sg. Besi, 57000 Kuala Lumpur, Website : www.bossil.com

Malaysia.

2. Hazard(s) identification

Substance/Mixture : Mixture

Hazard classification : Flam.Liq.3

: GHS02 Flame **Pictogram**

Signal word : Danger

Hazard statement(s)

H226 Flammable liquid and vapour.

<u>Precautionary statement(s)</u>: Not classified as hazardous

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P403+P235	Store in a well-ventilated place. Keep cool.

Other hazards which do not result in classification but contribute to overall hazards: None known



Safety Data Sheet

BS-3100 Vinyl Adhesive

Issued date: 23/12/16 Revision date: 06/06/18 Revision No.: 1

3. Composition/Information on ingredients

Chemical name	CAS No.	EINECS No.	%
Propanone	67-64-1	200-662-2	1 - 10

4. First-aid measures

In case of inhalation:

Remove to fresh air, keep warm and at rest. Contact physician if symptom persists.

In case of skin contact:

Remove contaminated clothing. Rinse with copious amount of water and soap. Get medical advice if skin irritation or a rash occurs. Wash clothing before reuse.

In case of eye contact:

Contact lenses should be removed. Rinse with copious amount of water immediately. Seek medical advice if eye irritation develops and persists.

In case of ingestion:

DO NOT induce vomiting. Rinse mouth thoroughly with water. Get medical attention if a symptom persists.

Personal protection equipment for first-aiders:

Pay attention to any potential hazards and use recommended personal protection equipment if potential for exposure exists.

Most important symptoms and effects, acute and delayed:

None known.

5. Fire-fighting measures

Suitable extinguishing media:

Water, alcohol-resistant foam, carbon dioxide, dry chemical.

Unsuitable extinguishing media:

None known.

Specific firefighting procedures:

Remove undamaged containers from fire area if it is safe to do so. Use extinguishing media that is suitable to local circumstances and surrounding environment.

Special person protection equipment for firefighters:

NIOSH-approved self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Specific hazards arising from firefighting:

Exposure to combustion products may be a hazard to health.

Thermal decomposition products:

Oxides of carbon.



Safety Data Sheet

BS-3100 Vinyl Adhesive

Issued date: 23/12/16 Revision date: 06/06/18 Revision No.: 1

6. Accidental release measures

Personal precautions, protective equipment and emergency procedure:

Use recommended personal protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Measure for cleaning/collecting:

Wipe or soak with inert liquid binding material (sand, sawdust, etc.). Scrape away cured material. Dispose the spilt material according to local or national regulations. Section 13 of this safety data sheet provides information regarding certain local or national requirements.

Additional information:

Prevent spillage from entering drainage/sewer systems. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

7. Handling and storage

Handling:

Ensure good ventilation during use. Avoid contact with skin and eyes. Do not eat, drink, or smoke when using the product.

Storage:

Ensure containers and cartridges are tightly closed. Store in a dry, well-ventilated area, and protected from direct sunlight with temperature not exceeding 30 °C. Keep away from incompatibles. Refer to section 10 for incompatible materials.

8. Exposure controls/personal protection

Components	CAS No.	Form of exposure (Value type)	Control Parameter	Basis
Propanone	67-64-1	8 hours TWA	1,187 mg/m ³	Malaysia OSHA
Propanone	67-64-1	8 hours TWA	2,400 mg/m ³	US OSHA
Propanone	67-64-1	8 hours TWA	1,210 mg/m ³	UK WEL
Propanone	67-64-1	8 hours TWA	1,185 mg/m ³	Safe Work Australia

Engineering controls:

Product curing may form hazardous compounds. Ensure adequate ventilation and minimise workplace exposure concentrations.

Industrial hygiene:

Remove immediately all contaminated clothing. Do not inhale vapour. Wash hands and contaminated areas with water and soap before leaving the work site. Change clothing before leaving workplace and wash before reuse. Do not eat, drink, or smoke while using product.

Hand protection:

Suitable impervious protective gloves (latex, nitrile, etc.). Breakthrough time is not tested for this product. Change gloves often if possible.

Bossil

BOSSIL TECHNOLOGY SDN. BHD.

Safety Data Sheet

BS-3100 Vinyl Adhesive

Issued date: 23/12/16 Revision date: 06/06/18 Revision No.: 1

Respiratory protection:

A NIOSH-approved respirator with filter for organic vapours is recommended where local ventilation is not adequate.

Eye/Face protection:

Protective goggles/safety glasses.

9. Physical and chemical properties

Appearance : Viscous liquid
Odour : Mild odour
Odour threshold : Not determined
pH : Not determined
Freezing/Melting point : Not determined
Boiling point range : Not applicable

Flash point : 31°C

Evaporation rate : Not applicable

Flammability : Not classified as flammable Explosive properties : Not classified as explosive Oxidising properties : Not classified as oxidising

Vapour pressure: Not applicableVapour density: Not applicableRelative density: Approx. 1.60Solubility in water: Soluble in water

N-octanol/water

partition coefficient : Not determinedDecomposition temperature : Not determinedViscosity : Not applicable

10. Stability and reactivity

Reactivity:

No reactive hazards known.

Stability:

Stable under recommended handling and storage conditions.

Conditions to avoid:

None known.

Hazardous reactions:

During normal storage, hazardous decomposition will not occur. At higher temperatures, decomposition products depend on the temperature, air supply and presence of other materials. Irritant gas and vapours will be produced.

Hazardous decomposition products:

None known.

Incompatible materials:

Strong oxidising agents.

11. Toxicology information



Safety Data Sheet

BS-3100 Vinyl Adhesive

Issued date: 23/12/16 Revision date: 06/06/18 Revision No.: 1

No specific oral, inhalation or dermal toxicology data is known for this product. Any toxicological data included in this section is based on the data associated with the components.

Acute oral toxicity, LD₅₀ (rat):

Not classified based on available information and/or concentration of components.

Propanone 5,800 mg/kg

Acute dermal toxicity, LD₅₀ (rabbit):

Not classified based on available information and/or concentration of components.

Propanone 7,400 mg/kg

Acute inhalation toxicity, LC₅₀ (6 hours, rat):

Not classified based on available information and/or concentration of components.

Serious eye damage/eye irritation:

Not classified based on available information and/or concentration of components.

Propanone Causes eye irritation.

Skin corrosion/skin irritation:

Not classified based on available information and/or concentration of components.

Propanone Not skin irritant.

Respiratory/Skin sensitisation:

Not classified based on available information and/or concentration of components.

Propanone Not sensitising on skin.

Germ cell mutagenicity:

Not classified based on available information and/or concentration of components.

Propanone Negative genotoxicity *in vitro*.
Negative genotoxicity *in vitro*.

Carcinogenicity:

Not classified based on available information and/or concentration of components.

Propanone Negative carcinogenicity.

Reproductive toxicity:

Not classified based on available information and/or concentration of components.

Propanone No effect on fertility and foetal development.

Specific target organ toxicity – single exposure:

Not classified based on available information and/or concentration of components.

Propanone May cause drowsiness and dizziness.

Specific target organ toxicity – repeated exposure:



Safety Data Sheet

BS-3100 Vinyl Adhesive

Issued date: 23/12/16 Revision date: 06/06/18 Revision No.: 1

Not classified based on available information and/or concentration of components.

	Exposure by oral on mouse for 13 weeks. LOAEL: 11,298 mg/kg bw/day
Propanone	Exposure by inhalation on rats for 8 weeks. NOAEC: 45,000 mg/m³

Aspiration toxicity:

Not classified based on available information and/or concentration of components.

Likely route of administration:

Skin contact and ingestion.

12. Ecological information

Individual components of this mixture have been independently tested by the raw material suppliers and any known results have been presented below. The results for the individual components may not be representative of the ecological toxicity of this finished product. This finished product has not been tested to determine individual toxicological/ecological limits.

Ecology toxicity:

No adverse effect on aquatic organisms is predicted based on available information and/or concentration of components.

Propanone	
Toxicity to fish	Exposure for 96 hours, LC ₅₀ : 6,210 mg/L
Toxicity to crustacean	Exposure for 48 hours, EC ₅₀ : 8,800 mg/L
Toxicity to algae or other aquatic plants	Exposure for 8 days, NOEC: 530 mg/L

Persistence and degradability:

Not likely to be persistent based on available information and/or concentration of components.

Propanone	Readily	biodegradable.
Fiopanone	Exposure for 20 days, 91% biodegrada	ation.

Bioaccumulative potential:

No bioaccumulation potential based on available information and/or concentration of components.

Propanone BCF: 3

Mobility in soil:

No data available.

13. Disposal information

Waste treatment/disposal methods - unused products

Waste disposal must be in compliance with environmental protection requirements and local regulations.

Waste treatment/disposal methods - contaminated packaging

Dispose of as unused product. Empty container should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Bossil

BOSSIL TECHNOLOGY SDN. BHD.

Safety Data Sheet

BS-3100 Vinyl Adhesive

Issued date: 23/12/16 Revision date: 06/06/18 Revision No.: 1

Road transport (UNRTDG):

UN number : UN1133

Proper shipping name: ADHESIVES containing flammable liquid

Technical name: Not applicable

Hazard class : 3 Classification code : F1 Packing group : III

Marine transport (IMDG):

UN number : UN1133

Proper shipping name: ADHESIVES containing flammable liquid

Technical name: Not applicable

Hazard class : 3

EmS : F-E, S-D Packing group : III

Marine pollutant : Not marine pollutant

Air transport (IATA):.

UN number : UN1133

Proper shipping name: ADHESIVES containing flammable liquid

Technical name: Not applicable

Hazard class : 3 Packing group : III

15. Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical in question:

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2010 (Malaysia)

Occupational Safety and Health (Classification, Labelling, and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 (Malaysia)

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (European Union)

Occupational Safety and Health Administration (OSHA) (2006) Air Contaminants. 29 CFR 1910.1000 (United States of America)

Work Health and Safety Act 2011 (Australia)

EH40/2005 Workplace exposure limits (United Kingdom)

Chemical inventory status:

Canada DSL/NDSL
China IECSC
Japan ENCS
Korea KECI
Philippines PICCS
United States TCSA

: All ingredients listed or exempt.

16. Other information

Definitions:

TWA: Time-weighted average.

Bossil

BOSSIL TECHNOLOGY SDN. BHD.

Safety Data Sheet

BS-3100 Vinyl Adhesive

Issued date: 23/12/16 Revision date: 06/06/18 Revision No.: 1

STEL: Short-term exposure level.

OSHA : Occupational Safe and Health Act

WEL: Workplace exposure limits

LD₅₀ : The minimum dose required for lethal effects in 50% of a given population of test specimens.

ppm : part per million
bw : body weight

NIOSH : National Institute for Occupational Safety and Health.

UNRTDG: United Nations Recommendations on the Transport of Dangerous Goods

IMDG : International Maritime Dangerous Goods
 IATA : International Air Transport Association
 AICS : Australian Inventory of Chemical Substances

DSL : Domestic Substance List
NDSL : Non-domestic Substances List

IECSC: Inventory of Existing Chemical Substances in China.

ENCS : Existing and New Chemical Substances. **KECI** : Korea Existing Chemicals Inventory.

PICCS: Philippines Inventory of Chemicals and Chemical Substances.

TSCA: Toxic Substances Control Act.

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist. The details contained herein are based on our present state of knowledge and experience in characterising our product with regard to any possible safety requirement at the date of its publication. We do, however, pass them on without any warranty or property assurances.