

Technical Data Sheet

BS-3200 Putty Filler



Features

- ♦ Quick Drying
- ♦ Virtually Non-shrinking
- ♦ Paintable
- ♦ Easy to Use

Available Colour

- ♦ White

Packaging

- ♦ 500 g / tub ~ 36 / carton
- ♦ 1.5 kg / tub ~ 12 / carton
- ♦ 5.0 kg / pail ~ 4 / carton

Product Specification

Specific Gravity	: 1.84 – 1.86
Solid Content	: 76 % - 78 %

Description

An easy-to-use multi-purpose filler specially formulated to fill cracks and gaps in a single application. It has virtually no shrinkage and is smooth and durable. It is paintable with oil and water based paints.

Applications

- ♦ Filling cracks and holes on surfaces without any structural movements (walls, ceilings, doors, windows, etc.).
- ♦ Can be used outdoor if painted over.

Direction

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Apply with spatula or scraper, push the filler firmly into the crack or hole.
3. Apply 1 – 2 layers depending on the extent of unevenness.
4. Allow 2 – 3 hours to set in 2 mm applications at 25 °C. Allow for longer drying times in thicker applications and colder weather.
5. Once set, sand smooth and paint over.
6. Clean up with a wet cloth. Replace cap after use and store in cool, dry place.

Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Storage

- ♦ Store in a dry and cool place with temperature below 30 °C.
- ♦ Use within 12 months from date of production

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.