

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

1. Identification of the substance/preparation and of the company/undertaking**Product name** : BS-510 All Pressure Solvent Cement**Product use** : Solvent-based adhesive**Company** : Bossil Technology Sdn. Bhd.
22A-1, Jalan Tasik Utama 10,
The Trillium @ Lake Fields,
Sg. Besi, 57000 Kuala Lumpur,
Malaysia.**Telephone** : +6016 - 2119190**Fax** : -**Email** : sales@bossil.com**Website** : www.bossil.com**2. Hazard(s) identification****Substance/Mixture** : Mixture**Hazard classification** : Flam.Liq.2

Skin Irrit.2

Eye Irrit.2

STOT SE 3

Pictogram

: GHS02



Flame



GHS07

Exclamation mark

Signal word

: Warning

Hazard statement(s):

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statement(s):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

P240	Ground container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with soap and water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P403+P233	Store in a well ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Other hazards which do not result in classification but contribute to overall hazards: None known**3. Composition/Information on ingredients**

Chemical name	CAS No.	EINECS No.	%
---------------	---------	------------	---

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Cyclohexanone	108-94-1	203-631-1	70 - 90
Butanone	78-93-3	201-159-0	
Tetrahydrofuran	109-99-9	203-726-8	
PVC resin	9002-86-2	-	10 - 30

4. First-aid measures**In case of inhalation:**

Remove to fresh air, keep warm and at rest. Contact physician if symptom persists.

In case of skin contact:

Remove contaminated clothing. Rinse with copious amount of water and soap. Get medical advice if skin irritation or a rash occurs. Wash clothing before reuse.

In case of eye contact:

Contact lenses should be removed. Rinse with copious amount of water immediately. Seek medical advice if eye irritation develops and persists.

In case of ingestion:

DO NOT induce vomiting. Rinse mouth thoroughly with water. Get medical attention if a symptom persists.

Personal protection equipment for first-aiders:

Pay attention to any potential hazards and use recommended personal protection equipment if potential for exposure exists.

Most important symptoms and effects, acute and delayed:

May cause skin and eye irritation. May cause drowsiness and dizziness.

5. Fire-fighting measures**Suitable extinguishing media:**

Alcohol-resistant foam, carbon dioxide, dry chemical.

Unsuitable extinguishing media:

None known.

Specific firefighting procedures:

Remove undamaged containers from fire area if it is safe to do so. Use extinguishing media that is suitable to local circumstances and surrounding environment.

Special person protection equipment for firefighters:

NIOSH-approved self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Specific hazards arising from firefighting:

Exposure to combustion products may be a hazard to health.

Thermal decomposition products:

Carbon dioxide, carbon monoxide, nitrogen oxides, and other irritant gases.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

6. Accidental release measures**Personal precautions, protective equipment and emergency procedure:**

Use recommended personal protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Measure for cleaning/collecting:

Wipe or soak with inert liquid binding material (sand, sawdust, etc.). Scrape away cured material. Dispose the spilt material according to local or national regulations. Section 13 of this safety data sheet provides information regarding certain local or national requirements.

Additional information:

Prevent spillage from entering drainage/sewer systems. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

7. Handling and storage**Handling:**

Ensure good ventilation during use. Avoid contact with skin and eyes. Do not eat, drink, or smoke when using the product.

Storage:

Ensure containers and cartridges are tightly closed. Store in a dry, well-ventilated area, and protected from direct sunlight with temperature not exceeding 30 °C. Keep away from incompatibles. Refer to section 10 for incompatible materials.

8. Exposure controls/personal protection

Components	CAS No.	Form of exposure (Value type)	Control Parameter	Basis
Cyclohexanone	108-94-1	8 hours TWA (skin)	100 mg/m ³	Malaysia OSHA
Cyclohexanone	108-94-1	8 hours TWA	200 mg/m ³	US OSHA
Cyclohexanone	108-94-1	8 hours TWA	39 mg/m ³	UK WEL
Cyclohexanone	108-94-1	8 hours TWA	100 mg/m ³	Safe Work Australia
Butanone	78-93-3	8 hours TWA	590 mg/m ³	Malaysia OSHA
Butanone	78-93-3	8 hours TWA	590 mg/m ³	US OSHA
Butanone	78-93-3	8 hours TWA	600 mg/m ³	UK WEL
Butanone	78-93-3	8 hours TWA	445 mg/m ³	Safe Work Australia
Tetrahydrofuran	109-99-9	8 hours TWA	590 mg/m ³	Malaysia OSHA

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Tetrahydrofuran	109-99-9	8 hours TWA	590 mg/m ³	US OSHA
Tetrahydrofuran	109-99-9	8 hours TWA	150 mg/m ³	UK WEL
Tetrahydrofuran	109-99-9	8 hours TWA	295 mg/m ³	Safe Work Australia

Engineering controls:

Product curing may form hazardous compounds. Ensure adequate ventilation and minimise workplace exposure concentrations.

Industrial hygiene:

Remove immediately all contaminated clothing. Do not inhale vapour. Wash hands and contaminated areas with water and soap before leaving the work site. Change clothing before leaving workplace and wash before reuse. Do not eat, drink, or smoke while using product.

Hand protection:

Suitable impervious protective gloves (neoprene, nitrile, etc.). Breakthrough time is not tested for this product. Change gloves often if possible.

Respiratory protection:

A NIOSH-approved respirator with filter for organic vapours is recommended where local ventilation is not adequate.

Eye/Face protection:

Protective goggles/safety glasses.

9. Physical and chemical properties

Appearance	: Viscous liquid
Odour	: Aromatic odour
Odour threshold	: Not determined
pH	: Not applicable
Freezing/Melting point	: Not determined
Boiling point range	: Not determined
Flash point	: <23 °C
Evaporation rate	: Not applicable
Flammability	: Highly flammable
Explosive properties	: Not classified as explosive
Oxidising properties	: Not classified as oxidising
Vapour pressure	: Not applicable
Vapour density	: Not applicable
Relative density	: Approximately 0.96
Solubility in water	: Insoluble
N-octanol/water partition coefficient	: Not determined
Decomposition temperature	: Not determined
Viscosity	: 1,000 - 1,600 cPs

10. Stability and reactivity**Reactivity:**

No reactive hazards known.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Stability:

Stable under recommended handling and storage conditions.

Conditions to avoid:

Avoid sources of ignition.

Hazardous reactions:

Hazardous polymerisation will not occur.

Hazardous decomposition products:

None known.

Incompatible materials:

Strong oxidising agents, acids, and sources of ignition.

11. Toxicology information

No specific oral, inhalation or dermal toxicology data is known for this product. Any toxicological data included in this section is based on the data associated with the components.

Acute oral toxicity, LD₅₀ (rat):

Not classified based on available information and/or concentration of components.

Cyclohexanone	1,890 mg/kg
Butanone	3,460 mg/kg
Tetrahydrofuran	1,650 mg/kg

Acute dermal toxicity, LD₅₀ (rabbit):

Not classified based on available information and/or concentration of components.

Cyclohexanone	>794 mg/kg
Butanone	>8,050 mg/kg
Tetrahydrofuran	>2,000 mg/kg

Acute inhalation toxicity, LC₅₀ (4 hours, rat):

Not classified based on available information and/or concentration of components.

Cyclohexanone	>6.2 mg/L
---------------	-----------

Serious eye damage/eye irritation:

Classified as an eye irritant.

Cyclohexanone	Causes eye irritation.
Butanone	Causes eye irritation.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Tetrahydrofuran	Causes eye irritation.
-----------------	------------------------

Skin corrosion/skin irritation:

Classified as a skin irritant.

Cyclohexanone	Causes skin irritation.
Butanone	Not skin irritant.
Tetrahydrofuran	Not skin irritant.

Respiratory/Skin sensitisation:

Not classified based on available information and/or concentration of components.

Cyclohexanone	Not sensitising on skin.
Butanone	Not sensitising on skin.
Tetrahydrofuran	Not sensitising on skin.

Germ cell mutagenicity:

Not classified based on available information and/or concentration of components.

Cyclohexanone	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .
Butanone	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .
Tetrahydrofuran	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .

Carcinogenicity:

Not classified based on available information and/or concentration of components.

Cyclohexanone	Marginal/weak evidence of carcinogenic activity.
---------------	--

Reproductive toxicity:

Not classified based on available information and/or concentration of components.

Cyclohexanone	No effect on fertility and foetal development.
Butanone	No effect on fertility. Maternal toxicity, NOAEC: 1,002 ppm
Tetrahydrofuran	No effect on fertility. Parental rats exposed to high concentration showed reduced body weight of offspring. NOAEL: 1,800 ppm

Specific target organ toxicity – single exposure:

Classified as having narcotic effects.

Butanone	May cause drowsiness and dizziness.
----------	-------------------------------------

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Tetrahydrofuran	May cause drowsiness and dizziness.
-----------------	-------------------------------------

Specific target organ toxicity – repeated exposure:

Not classified based on available information and/or concentration of components.

Cyclohexanone	Exposure by oral on rats for 3 months. NOAEL: 143 mg/kg bw/day
Butanone	Exposure by inhalation on rats for 90 days. NOAEC: 5,014 ppm
Tetrahydrofuran	Exposure by oral on rats for 4 weeks. NOAEL: 111.3 mg/kg bw/day
	Exposure by inhalation on mouse for 14 weeks. NOAEC: 200 ppm

Aspiration toxicity:

Not classified based on available information and/or concentration of components.

Likely route of administration:

Inhalation, skin contact, and ingestion.

12. Ecological information

Individual components of this mixture have been independently tested by the raw material suppliers and any known results have been presented below. The results for the individual components may not be representative of the ecological toxicity of this finished product. This finished product has not been tested to determine individual toxicological/ecological limits.

Ecology toxicity:

No adverse effect on aquatic organisms is predicted based on available information and/or concentration of components.

Cyclohexanone Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC ₅₀ : 527-732mg/L Exposure for 24 hours, EC ₅₀ : 800 mg/L Exposure for 72 hours, EC ₅₀ : 32.9 mg/L
Butanone Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC ₅₀ : 2,993 mg/L Exposure for 48 hours, EC ₅₀ : 308 mg/L Exposure for 72 hours, EC ₅₀ : 1,972 mg/L
Tetrahydrofuran Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC ₅₀ : 2,160 mg/L Exposure for 24 hours, EC ₅₀ : 3,485 ppm Exposure for 8 days, TTC: 3,700 mg/L

Persistence and degradability:

Not likely to be persistent based on available information and/or concentration of components.

Cyclohexanone	Readily biodegradable. Exposure for 14 days, >90% biodegradation.
Butanone	Readily biodegradable. Exposure for 28 days, 98% biodegradation.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Tetrahydrofuran

Not readily biodegradable in 28 days, but biodegradable if exposed for longer periods of time.
Exposure for 28 days, 39% biodegradation.
Exposure for 52 days, 61% biodegradation.

Bioaccumulative potential:

No bioaccumulation potential based on available information and/or concentration of components.

Mobility in soil:

No data available.

13. Disposal information**Waste treatment/disposal methods - unused products**

Waste disposal must be in compliance with environmental protection requirements and local regulations.

Waste treatment/disposal methods - contaminated packaging

Dispose of as unused product. Empty container should be taken to an approved waste handling site for recycling or disposal.

14. Transport information**Road transport (UNRTDG):**

UN number : UN1133
Proper shipping name : ADHESIVES containing flammable liquid
Technical name : Not applicable
Hazard class : 3
Classification code : F1
Packing group : II

Marine transport (IMDG):

UN number : UN1133
Proper shipping name : ADHESIVES containing flammable liquid
Technical name : Not applicable
Hazard class : 3
EmS : F-E, S-D
Packing group : II
Marine pollutant : Not marine pollutant

Air transport (IATA):

UN number : UN1133
Proper shipping name : ADHESIVES containing flammable liquid
Technical name : Not applicable
Hazard class : 3
Packing group : II

15. Regulatory information**Safety, health, and environmental regulations specific for the hazardous chemical in question:**

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2010 (Malaysia)

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-510
All Pressure Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Occupational Safety and Health (Classification, Labelling, and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 (Malaysia)

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (European Union)

Occupational Safety and Health Administration (OSHA) (2006) Air Contaminants. 29 CFR 1910.1000 (United States of America)

Work Health and Safety Act 2011 (Australia)

EH40/2005 Workplace exposure limits (United Kingdom)

Chemical inventory status:

Australia AICS	: All ingredients listed or exempt.
Canada DSL	: All ingredients listed or exempt.
China IECSC	: All ingredients listed or exempt.
Japan ENCS	: All ingredients listed or exempt.
Korea KECI	: All ingredients listed or exempt.
Philippines PICCS	: All ingredients listed or exempt.
United States TCSA	: All ingredients listed or exempt.

16. Other information**Definitions:**

TWA	: Time-weighted average.
STEL	: Short-term exposure level.
OSHA	: Occupational Safe and Health Act
WEL	: Workplace exposure limits
LD₅₀	: The minimum dose required for lethal effects in 50% of a given population of test specimens.
ppm	: part per million
bw	: body weight
BCF	: Bioconcentration factor
NOAEL	: No-observed-adverse-effect-level
LOAEL	: Lowest-observed-adverse-effect level
NIOSH	: National Institute for Occupational Safety and Health.
UNRTDG	: United Nations Recommendations on the Transport of Dangerous Goods
IMDG	: International Maritime Dangerous Goods
IATA	: International Air Transport Association
AICS	: Australian Inventory of Chemical Substances
DSL	: Domestic Substance List
ENCS	: Existing and New Chemical Substances.
KECI	: Korea Existing Chemicals Inventory.
ECSN	: Existing Chemical Substance Nomination.
TSCA	: Toxic Substances Control Act

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist. The details contained herein are based on our present state of knowledge and experience in characterising our product with regard to any possible safety requirement at the date of its publication. We do, however, pass them on without any warranty or property assurances.