

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**1. Identification of the substance/preparation and of the company/undertaking****Product name** : BS-512G / BS-512T Heavy Duty Solvent Cement**Product use** : Solvent-based adhesive**Company** : Bossil Technology Sdn. Bhd.  
22A-1, Jalan Tasik Utama 10,  
The Trillium @ Lake Fields,  
Sg. Besi, 57000 Kuala Lumpur,  
Malaysia.**Telephone** : +6016 - 2119190**Fax** : -**Email** : sales@bossil.com**Website** : www.bossil.com**2. Hazard(s) identification****Substance/Mixture** : Mixture**Hazard classification** : Flam.Liq.2

Eye Irrit.2

STOT SE 3

**Pictogram**

: GHS02



Flame



GHS07

Exclamation mark

**Signal word**

: Warning

**Hazard statement(s):**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Precautionary statement(s):**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313	If eye irritation persists get medical advice/attention.
P403+P233	Store in a well ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Other hazards which do not result in classification but contribute to overall hazards:** None known**3. Composition/Information on ingredients**

Chemical name	CAS No.	EINECS No.	%
Cyclohexanone	108-94-1	203-631-1	70 - 90
Butanone	78-93-3	201-159-0	
Tetrahydrofuran	109-99-9	203-726-8	
PVC resin	9002-86-2	-	10 - 30
Epoxy resin (number average molecular weight $\leq$ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	25068-38-6	500-033-5	1 - 10

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**4. First-aid measures****In case of inhalation:**

Remove to fresh air, keep warm and at rest. Contact physician if symptom persists.

**In case of skin contact:**

Remove contaminated clothing. Rinse with copious amount of water and soap. Get medical advice if skin irritation or a rash occurs. Wash clothing before reuse.

**In case of eye contact:**

Contact lenses should be removed. Rinse with copious amount of water immediately. Seek medical advice if eye irritation develops and persists.

**In case of ingestion:**

DO NOT induce vomiting. Rinse mouth thoroughly with water. Get medical attention if a symptom persists.

**Personal protection equipment for first-aiders:**

Pay attention to any potential hazards and use recommended personal protection equipment if potential for exposure exists.

**Most important symptoms and effects, acute and delayed:**

May cause eye irritation. May cause drowsiness and dizziness.

**5. Fire-fighting measures****Suitable extinguishing media:**

Alcohol-resistant foam, carbon dioxide, dry chemical.

**Unsuitable extinguishing media:**

None known.

**Specific firefighting procedures:**

Remove undamaged containers from fire area if it is safe to do so. Use extinguishing media that is suitable to local circumstances and surrounding environment.

**Special person protection equipment for firefighters:**

NIOSH-approved self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Specific hazards arising from firefighting:**

Exposure to combustion products may be a hazard to health.

**Thermal decomposition products:**

Carbon dioxide, carbon monoxide, nitrogen oxides, and other irritant gases.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedure:**

Use recommended personal protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

**Measure for cleaning/collecting:**

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Wipe or soak with inert liquid binding material (sand, sawdust, etc.). Scrape away cured material. Dispose the spilt material according to local or national regulations. Section 13 of this safety data sheet provides information regarding certain local or national requirements.

**Additional information:**

Prevent spillage from entering drainage/sewer systems. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

**7. Handling and storage****Handling:**

Ensure good ventilation during use. Avoid contact with skin and eyes. Do not eat, drink, or smoke when using the product.

**Storage:**

Ensure containers and cartridges are tightly closed. Store in a dry, well-ventilated area, and protected from direct sunlight with temperature not exceeding 30 °C. Keep away from incompatibles. Refer to section 10 for incompatible materials.

**8. Exposure controls/personal protection**

Components	CAS No.	Form of exposure (Value type)	Control Parameter	Basis
Cyclohexanone	108-94-1	8 hours TWA (skin)	100 mg/m <sup>3</sup>	Malaysia OSHA
Cyclohexanone	108-94-1	8 hours TWA	200 mg/m <sup>3</sup>	US OSHA
Cyclohexanone	108-94-1	8 hours TWA	39 mg/m <sup>3</sup>	UK WEL
Cyclohexanone	108-94-1	8 hours TWA	100 mg/m <sup>3</sup>	Safe Work Australia
Butanone	78-93-3	8 hours TWA	590 mg/m <sup>3</sup>	Malaysia OSHA
Butanone	78-93-3	8 hours TWA	590 mg/m <sup>3</sup>	US OSHA
Butanone	78-93-3	8 hours TWA	600 mg/m <sup>3</sup>	UK WEL
Butanone	78-93-3	8 hours TWA	445 mg/m <sup>3</sup>	Safe Work Australia
Tetrahydrofuran	109-99-9	8 hours TWA	590 mg/m <sup>3</sup>	Malaysia OSHA
Tetrahydrofuran	109-99-9	8 hours TWA	590 mg/m <sup>3</sup>	US OSHA
Tetrahydrofuran	109-99-9	8 hours TWA	150 mg/m <sup>3</sup>	UK WEL
Tetrahydrofuran	109-99-9	8 hours TWA	295 mg/m <sup>3</sup>	Safe Work Australia

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**Engineering controls:**

Product curing may form hazardous compounds. Ensure adequate ventilation and minimise workplace exposure concentrations.

**Industrial hygiene:**

Remove immediately all contaminated clothing. Do not inhale vapour. Wash hands and contaminated areas with water and soap before leaving the work site. Change clothing before leaving workplace and wash before reuse. Do not eat, drink, or smoke while using product.

**Hand protection:**

Suitable impervious protective gloves (neoprene, nitrile, etc.). Breakthrough time is not tested for this product. Change gloves often if possible.

**Respiratory protection:**

A NIOSH-approved respirator with filter for organic vapours is recommended where local ventilation is not adequate.

**Eye/Face protection:**

Protective goggles/safety glasses.

**9. Physical and chemical properties**

<b>Appearance</b>	: Viscous liquid
<b>Odour</b>	: Aromatic odour
<b>Odour threshold</b>	: Not determined
<b>pH</b>	: Not applicable
<b>Freezing/Melting point</b>	: Not determined
<b>Boiling point range</b>	: Not determined
<b>Flash point</b>	: <23 °C
<b>Evaporation rate</b>	: Not applicable
<b>Flammability</b>	: Highly flammable
<b>Explosive properties</b>	: Not classified as explosive
<b>Oxidising properties</b>	: Not classified as oxidising
<b>Vapour pressure</b>	: Not applicable
<b>Vapour density</b>	: Not applicable
<b>Relative density</b>	: Approximately 0.90
<b>Solubility in water</b>	: Insoluble
<b>N-octanol/water partition coefficient</b>	: Not determined
<b>Decomposition temperature</b>	: Not determined
<b>Viscosity</b>	: 1,400 - 2,000 cPs

**10. Stability and reactivity****Reactivity:**

No reactive hazards known.

**Stability:**

Stable under recommended handling and storage conditions.

**Conditions to avoid:**

Avoid sources of ignition.

**Hazardous reactions:**

Hazardous polymerisation will not occur.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**Hazardous decomposition products:**

None known.

**Incompatible materials:**

Strong oxidising agents, acids, and sources of ignition.

**11. Toxicology information**

No specific oral, inhalation or dermal toxicology data is known for this product. Any toxicological data included in this section is based on the data associated with the components.

**Acute oral toxicity, LD<sub>50</sub> (rat):**

Not classified based on available information and/or concentration of components.

Cyclohexanone	1,890 mg/kg
Butanone	3,460 mg/kg
Tetrahydrofuran	1,650 mg/kg
Epoxy resin (number average molecular weight ≤ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	>15,000 mg/kg

**Acute dermal toxicity, LD<sub>50</sub> (rabbit):**

Not classified based on available information and/or concentration of components.

Cyclohexanone	>794 mg/kg
Butanone	>8,050 mg/kg
Tetrahydrofuran	>2,000 mg/kg
Epoxy resin (number average molecular weight ≤ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	>23,000 mg/kg

**Acute inhalation toxicity, LC<sub>50</sub> (4 hours, rat):**

Not classified based on available information and/or concentration of components.

Cyclohexanone	>6.2 mg/L
---------------	-----------

**Serious eye damage/eye irritation:**

Classified as an eye irritant.

Cyclohexanone	Causes eye irritation.
Butanone	Causes eye irritation.
Tetrahydrofuran	Causes eye irritation.
Epoxy resin (number average molecular weight ≤ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	Causes eye irritation.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**Skin corrosion/skin irritation:**

Not classified based on available information and/or concentration of components.

Cyclohexanone	Causes skin irritation.
Butanone	Not skin irritant.
Tetrahydrofuran	Not skin irritant.
Epoxy resin (number average molecular weight $\leq$ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	Causes skin irritation.

**Respiratory/Skin sensitisation:**

Not classified based on available information and/or concentration of components.

Cyclohexanone	Not sensitising on skin.
Butanone	Not sensitising on skin.
Tetrahydrofuran	Not sensitising on skin.
Epoxy resin (number average molecular weight $\leq$ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	Causes skin sensitisation.

**Germ cell mutagenicity:**

Not classified based on available information and/or concentration of components.

Cyclohexanone	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .
Butanone	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .
Tetrahydrofuran	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .
Epoxy resin (number average molecular weight $\leq$ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .

**Carcinogenicity:**

Not classified based on available information and/or concentration of components.

Cyclohexanone	Marginal/weak evidence of carcinogenic activity.
Epoxy resin (number average molecular weight $\leq$ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	Marginal/weak evidence of carcinogenic activity.

**Reproductive toxicity:**

Not classified based on available information and/or concentration of components.

Cyclohexanone	No effect on fertility and foetal development.
Butanone	No effect on fertility. Maternal toxicity, NOAEC: 1,002 ppm

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Tetrahydrofuran	No effect on fertility. Parental rats exposed to high concentration showed reduced body weight of offspring. NOAEL: 1,800 ppm
Epoxy resin (number average molecular weight $\leq$ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	No effect on fertility and foetal development.

**Specific target organ toxicity – single exposure:**

Classified as having narcotic effects.

Butanone	May cause drowsiness and dizziness.
Tetrahydrofuran	May cause drowsiness and dizziness.

**Specific target organ toxicity – repeated exposure:**

Not classified based on available information and/or concentration of components.

Cyclohexanone	Exposure by oral on rats for 3 months. NOAEL: 143 mg/kg bw/day
Butanone	Exposure by inhalation on rats for 90 days. NOAEC: 5,014 ppm
Tetrahydrofuran	Exposure by oral on rats for 4 weeks. NOAEL: 111.3 mg/kg bw/day Exposure by inhalation on mouse for 14 weeks. NOAEC: 200 ppm

**Aspiration toxicity:**

Not classified based on available information and/or concentration of components.

**Likely route of administration:**

Inhalation, skin contact, and ingestion.

**12. Ecological information**

Individual components of this mixture have been independently tested by the raw material suppliers and any known results have been presented below. The results for the individual components may not be representative of the ecological toxicity of this finished product. This finished product has not been tested to determine individual toxicological/ecological limits.

**Ecology toxicity:**

No adverse effect on aquatic organisms is predicted based on available information and/or concentration of components.

Cyclohexanone Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : 527-732mg/L Exposure for 24 hours, EC <sub>50</sub> : 800 mg/L Exposure for 72 hours, EC <sub>50</sub> : 32.9 mg/L
Butanone Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : 2,993 mg/L Exposure for 48 hours, EC <sub>50</sub> : 308 mg/L Exposure for 72 hours, EC <sub>50</sub> : 1,972 mg/L



**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Tetrahydrofuran Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : 2,160 mg/L Exposure for 24 hours, EC <sub>50</sub> : 3,485 ppm Exposure for 8 days, TTC: 3,700 mg/L
Epoxy resin (number average molecular weight ≤ 700) Reaction product of Bisphenol-A-(epichlorohydrin) Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : 2 mg/L Exposure for 48 hours, EC <sub>50</sub> : 1.8 mg/L Exposure for 72 hours, EC <sub>50</sub> : 11 mg/L

**Persistence and degradability:**

Not likely to be persistent based on available information and/or concentration of components.

Cyclohexanone	Readily biodegradable. Exposure for 14 days, >90% biodegradation.
Butanone	Readily biodegradable. Exposure for 28 days, 98% biodegradation.
Tetrahydrofuran	Not readily biodegradable in 28 days, but biodegradable if exposed for longer periods of time. Exposure for 28 days, 39% biodegradation. Exposure for 52 days, 61% biodegradation.
Epoxy resin (number average molecular weight ≤ 700) Reaction product of Bisphenol-A-(epichlorohydrin)	Not readily biodegradable, but significant hydrolysis observed. Exposure for 28 days, 12% biodegradation, >82% hydrolysis.

**Bioaccumulative potential:**

No bioaccumulation potential based on available information and/or concentration of components.

**Mobility in soil:**

No data available.

**13. Disposal information****Waste treatment/disposal methods - unused products**

Waste disposal must be in compliance with environmental protection requirements and local regulations.

**Waste treatment/disposal methods - contaminated packaging**

Dispose of as unused product. Empty container should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information****Road transport (UNRTDG):**

UN number : UN1133  
Proper shipping name : ADHESIVES containing flammable liquid  
Technical name : Not applicable  
Hazard class : 3  
Classification code : F1  
Packing group : II

**Marine transport (IMDG):**

UN number : UN1133

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**Proper shipping name** : ADHESIVES containing flammable liquid  
**Technical name** : Not applicable  
**Hazard class** : 3  
**EmS** : F-E, S-D  
**Packing group** : II  
**Marine pollutant** : Not marine pollutant

**Air transport (IATA):**

**UN number** : UN1133  
**Proper shipping name** : ADHESIVES containing flammable liquid  
**Technical name** : Not applicable  
**Hazard class** : 3  
**Packing group** : II

**15. Regulatory information****Safety, health, and environmental regulations specific for the hazardous chemical in question:**

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2010 (Malaysia)

Occupational Safety and Health (Classification, Labelling, and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 (Malaysia)

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (European Union)

Occupational Safety and Health Administration (OSHA) (2006) Air Contaminants. 29 CFR 1910.1000 (United States of America)

Work Health and Safety Act 2011 (Australia)

EH40/2005 Workplace exposure limits (United Kingdom)

**Chemical inventory status:**

Australia AICS : All ingredients listed or exempt.  
Canada DSL : All ingredients listed or exempt.  
China IECSC : All ingredients listed or exempt.  
Japan ENCS : All ingredients listed or exempt.  
Korea KECI : All ingredients listed or exempt.  
Philippines PICCS : All ingredients listed or exempt.  
United States TCSA : All ingredients listed or exempt.

**16. Other information****Definitions:**

**TWA** : Time-weighted average.  
**STEL** : Short-term exposure level.  
**OSHA** : Occupational Safe and Health Act  
**WEL** : Workplace exposure limits  
**LD<sub>50</sub>** : The minimum dose required for lethal effects in 50% of a given population of test specimens.  
**ppm** : part per million  
**bw** : body weight  
**BCF** : Bioconcentration factor  
**NOAEL** : No-observed-adverse-effect-level  
**LOAEL** : Lowest-observed-adverse-effect level

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-512G, BS-512T  
Heavy Duty Solvent Cement**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

<b>NIOSH</b>	: National Institute for Occupational Safety and Health.
<b>UNRTDG</b>	: United Nations Recommendations on the Transport of Dangerous Goods
<b>IMDG</b>	: International Maritime Dangerous Goods
<b>IATA</b>	: International Air Transport Association
<b>AICS</b>	: Australian Inventory of Chemical Substances
<b>DSL</b>	: Domestic Substance List
<b>ENCS</b>	: Existing and New Chemical Substances.
<b>KECI</b>	: Korea Existing Chemicals Inventory.
<b>ECSN</b>	: Existing Chemical Substance Nomination.
<b>TSCA</b>	: Toxic Substances Control Act

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist. The details contained herein are based on our present state of knowledge and experience in characterising our product with regard to any possible safety requirement at the date of its publication. We do, however, pass them on without any warranty or property assurances.