

	BOSSIL TECHNOLOGY SDN. BHD.	Issued Date: 11/05/11 Revision No: 1 Revision Date: 06/05/15 Page: 1 of 1
	Technical Data Sheet	
	BS-8300V / BS-8301 / BS-8302 All Purpose Adhesive	

Product Specification:

Colour	Clear
Working Time	5 – 15 minutes
Specific Gravity	0.80 ± 0.03
Solid Content	37 ± 1 %
Viscosity	medium
Shelf Life	12 Months

Product Description:

A clear color all purpose adhesive suitable for nearly all types of household repair and craft works. It is fast curing and will not attack the Polystyrene, and particularly applicable for visible adhesive joints and transparent materials.

Applications:

Ideal bonding applications: Bonds wood, cardboard, paper, fabric, leather, pottery, glass, china, marble, metal, felt, straw, hard foam and many types of plastic.

Directions:

1. Before applied, the surfaces must be clean, dry without foreign matter such as grease and oil, dirt and dust, blistering and loose layers of old paint and other residue.
2. Apply the adhesive to both surfaces if the material is absorbent. Press together firmly and leave to dry.
3. Replace cap after use and store in cool, dry place.
4. Cleaning after use can be done by using organic solvent, such as toluene.

Caution:

Avoid contact with skin and eyes. Skin contact may cause sensitisation. In case of eye or mouth contact, flush with cold water for 15 minutes and seek medical attention if feel unwell.

Storage:

Store in a dry and cool place. Below 30 °C gives optimum storage stability.



Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of various of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- END -