



SAFETY DATA SHEET

BS-8638 MS SEAM SEALANT

Page: 1

Compilation date: 11/05/2018

Revision date: 21/01/2020

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BS-8638 MS SEAM SEALANT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Bossil Technology Sdn. Bhd.
Lot 165, Jalan Industri 1/2,
Rawang Integrated Industrial Park,
Rawang,
Selangor,
48000
Malaysia.

Tel: +6016-2119190

Email: sales@bossil.com

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: -: EUH208

Most important adverse effects: Contains n-(3-(trimethoxysilyl)propyl)ethylenediamine, dibutylbis(pentane-2,4-dionato,o,o')tin. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains n-(3-(trimethoxysilyl)propyl)ethylenediamine, dibutylbis(pentane-2,4-dionato,o,o')tin. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

[cont...]

SAFETY DATA SHEET

BS-8638 MS SEAM SEALANT

Page: 2

Hazardous ingredients:

LIMESTONE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-279-6	1317-65-3	Substance with a Community workplace exposure limit.	-	50-70%

DIISONONYLPHTHALATE - REACH registered number(s): 01-2119432682-41-0000

271-090-9	68515-48-0	Substance with a Community workplace exposure limit.	-	10-30%
-----------	------------	--	---	--------

VINYLTRIMETHOXYSILANE

220-449-8	2768-02-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; STOT RE 2: H373	<1%
-----------	-----------	---	---	-----

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE

217-164-6	1760-24-3	-	Eye Dam. 1: H318; Skin Sens. 1B: H317	<1%
-----------	-----------	---	---------------------------------------	-----

DIBUTYLBIS(PENTANE-2,4-DIONATO,O,O')TIN

245-152-0	22673-19-4	-	Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Muta. 2: H341; Repr. 1A: H360; STOT SE 1: H370; STOT RE 1: H372; Aquatic Chronic 1: H410	<1%
-----------	------------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

[cont...]

SAFETY DATA SHEET

BS-8638 MS SEAM SEALANT

Page: 3

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

LIMESTONE

Workplace exposure limits:

Respirable dust

State	Workplace exposure limits		Respirable dust	
	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	10 mg/m ³	-	4 mg/m ³	-

[cont...]

SAFETY DATA SHEET

BS-8638 MS SEAM SEALANT

Page: 4

DIISONONYLPHTHALATE

UK	5 mg/m ³	-	-	-
----	---------------------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Dark green

Odour: Odourless

Evaporation rate: Not applicable.

Oxidising: Not applicable.

Boiling point/range°C: Not applicable.

Flash point°C: No data available.

Melting point/range°C: Not applicable.

Relative density: 1.57 g/ml

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

[cont...]

SAFETY DATA SHEET

BS-8638 MS SEAM SEALANT

Page: 5

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

LIMESTONE

ORAL	RAT	LD50	2000	mg/kg
------	-----	------	------	-------

DIISONONYLPHTHALATE

DERMAL	RBT	LD50	3160	mg/kg
DUST/MIST	RAT	4H LC50	4.4	mg/l
ORAL	RAT	LD50	10000	mg/kg

VINYLTRIMETHOXYSILANE

DERMAL	RBT	LD50	3259	mg/kg
ORAL	RAT	LD50	7120	mg/kg
VAPOURS	RAT	4H LC50	16.8	mg/l

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE

DERMAL	RBT	LD50	2000	mg/kg
DUST/MIST	RAT	4H LC50	1.49	mg/l
ORAL	RAT	LD50	2295	mg/kg

Excluded hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	-	No hazard: calculated
Acute toxicity (ac. tox. 3)	-	No hazard: calculated
Acute toxicity (ac. tox. 2)	-	No hazard: calculated
Acute toxicity (ac. tox. 1)	-	No hazard: calculated
Skin corrosion/irritation	-	No hazard: calculated
Serious eye damage/irritation	-	No hazard: calculated
Respiratory/skin sensitisation	-	No hazard: calculated
Germ cell mutagenicity	-	No hazard: calculated
Carcinogenicity	-	No hazard: calculated
Reproductive toxicity	-	No hazard: calculated

[cont...]

SAFETY DATA SHEET

BS-8638 MS SEAM SEALANT

Page: 6

STOT-single exposure	-	No hazard: calculated
STOT-repeated exposure	-	No hazard: calculated
Aspiration hazard	-	No hazard: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

LIMESTONE

Daphnia magna	48H EC50	100	mg/l
FISH	96H LC50	100	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	14	mg/l

DIISONONYLPHTHALATE

Daphnia magna	48H EC50	74	mg/l
Scenedesmus Subspicatus	72H ErC50	88	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	102	mg/l

VINYLTRIMETHOXYSILANE

Daphnia magna	48H EC50	168.7	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	89	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	191	mg/l

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE

Daphnia magna	48H EC50	81	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	8.8	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	597	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

[cont...]

SAFETY DATA SHEET

BS-8638 MS SEAM SEALANT

Page: 7

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H226: Flammable liquid and vapour.
H302: Harmful if swallowed.
H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H332: Harmful if inhaled.
H341: Suspected of causing genetic defects.
H360: May damage fertility or the unborn child.
H370: Causes damage to organs.

[cont...]

SAFETY DATA SHEET
BS-8638 MS SEAM SEALANT

Page: 8

H372: Causes damage to organs through prolonged or repeated exposure.

H373: May cause damage to organs ([bladder]) through prolonged or repeated exposure ([oral]).

H410: Very toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.