

# Technical Data Sheet

## BS-8182 Insulation Cork Tape



### Features

- ◆ Good Adhesion
- ◆ Remain Flexible
- ◆ Excellent Heat Insulation

### Available color

- ◆ Black

### Packaging

- ◆ 50 mm x 3 mm x 7.62 m~10/carton
- ◆ 50 mm x 3 mm x 9.14 m~10/carton

### Storage

- ◆ Store in a dry and cool place with temperature below 30 °C
- ◆ Use within 12 months from date of production

## Product Specification

Appearance	: Tacky, Rubbery Band
Specific Gravity	: 1.1 ± 0.1
Elongation	: ~100 %
Heat Resistance	: Good
Water Resistance	: Excellent
Service Temperature	: -20 °C to 90 °C

## Description

The heat insulation tape was specially formulated to insulate ducts and pipes for the refrigeration and air-conditioning industry. It is non-toxic, and has good adhesion on most piping and ducting materials, and it been asbestos-free.

## Applications

Ideal for heat insulation of pipes and ducts. Suitable for applications where water condensation is observed on refrigerant lines and cold pipes for air-conditioning system. It can be used as an excellent insulator for hot pipes, gasketing material, and to wrap valves, tees and fittings. It can also be used as a sound-deadening material.

## Directions

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Cut into a convenient length from the roll and remove release paper while wrapping tape spirally around pipe or fitting.
3. Tighten coil and press edges together.
4. Avoid stretching the tape.

## Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.