Bossi	BOSSIL TECHNOLOGY SDN. BHD. Safety Data Sheet BS-3360		
	١	Wood & Parquet A	Adhesive
Issued date: 08/05/17	ued date: 08/05/17 Revision date: - Revision No.: 0		
1. Identification of the substance/preparation and of the company/undertaking			
22A-1, Jalar The Trillium	d adhesive nology Sdn. Bhd. n TasikUtama 10, @ Lake Fields, 000 Kuala Lumpur,	Telephone Fax Email Website	: +6016 - 2119190 : - : sales@bossil.com : www.bossil.com
ubstance/Mixture	:Mixture		
azard classification	:Not classified as hazardous		
Pictogram	: Not classified as hazardous		
Signal word	:Not classified as hazardous		
	:Not classified as hazardous		
lazard statement(s)	:Not classified as haza	ardous	
	:Not classified as haza		

3. Composition/Information on ingredients

Chemical name	CAS No.	EINECS No.	%
Limestone	1317-65-3	215-279-6	10 - 30
Methanol	67-56-1	200-659-6	0.1 – 1.0

4. First-aid measures

In case of inhalation:

Remove to fresh air, keep warm and at rest. Contact physician if symptom persists.

In case of skin contact:

Remove contaminated clothing. Rinse with copious amount of water and soap. Get medical advice if skin irritation or a rash occurs. Wash clothing before reuse.

In case of eye contact:

Contact lenses should be removed. Rinse with copious amount of water immediately. Seek medical advice if eye irritation develops and persists.

In case of ingestion:

DO NOT induce vomiting. Rinse mouth thoroughly with water. Get medical attention if a symptom persists.



Safety Data Sheet

BS-3360

Wood & Parquet Adhesive

Issued date: 08/05/17

Revision date: -

Revision No.: 0

Personal protection equipment for first-aiders:

Pay attention to any potential hazards and use recommended personal protection equipment if potential for exposure exists.

Most important symptoms and effects, acute and delayed:

None known.

5. Fire-fighting measures

Suitable extinguishing media:

Water, alcohol-resistant foam, carbon dioxide,dry chemical.

Unsuitable extinguishing media:

None known.

Specificfirefighting procedures:

Remove undamaged containers from fire area if it is safe to do so. Use extinguishing media that is suitable to local circumstances and surrounding environment.

Special person protection equipment for firefighters:

NIOSH-approved self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Specific hazards arising from firefighting:

Exposure to combustion products may be a hazard to health.

Thermal decomposition products:

Oxides of carbon.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedure:

Use recommendedpersonal protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Measure for cleaning/collecting:

Wipe or soak with inert liquid binding material (sand, sawdust, etc.).Scrape away cured material. Dispose the spilt material according to local or national regulations. Section 13 of this safety data sheet provides information regarding certain local or national requirements.

Additional information:

Prevent spillage from entering drainage/sewer systems. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

7. Handling and storage

Handling:

Ensure good ventilation during use. Avoid contact with skin and eyes. Do not eat, drink, or smoke when using the product.

Storage:

Ensure containers and cartridgesare tightly closed. Store in a dry, well-ventilated area, and protected from direct sunlight with temperature not exceeding 30 °C. Keep away from incompatibles. Refer to section 10 for incompatible materials.



Safety Data Sheet

BS-3360

Wood & Parquet Adhesive

Issued date: 08/05/17

Revision date: -

Revision No.: 0

8. Exposure controls/personal protection

Components	CAS No.	Form of exposure (Value type)	Control Parameter	Basis
Limestone	1317-62-3	8 hours TWA (Particulate matter containing no asbestos and <1% crystalline silica)	10 mg/m ³	Malaysia OSHA
Limestone (total dust)	1317-62-3	8 hours TWA	10 mg/m ³	US OSHA
Limestone (respirable fraction)	1317-62-3	8 hours TWA	5 mg/m ³	US OSHA
Limestone (inhalable dust)	1317-62-3	8 hours TWA	10 mg/m ³	UK WEL
Limestone (respirable dust)	1317-62-3	8 hours TWA	4 mg/m ³	UK WEL
Limestone	1317-62-3	8 hours TWA (Particulate matter containing no asbestos and <1% crystalline silica)	10 mg/m ³	Safe Work Australia
Methanol	67-56-1	8 hours TWA	262 mg/m ³	Malaysia OSHA
Methanol	67-56-1	8 hours TWA	260 mg/m ³	US OSHA
Methanol	67-56-1	8 hours TWA	266 mg/m ³	UK WEL
Methanol	67-56-1	8 hours TWA	262 mg/m ³	Safe Work Australia

Engineering controls:

Product curing may form hazardous compounds. Ensure adequate ventilation and minimise workplace exposure concentrations.

Industrial hygiene:

Remove immediately all contaminated clothing. Do not inhale vapour. Wash hands and contaminated areas with water and soap before leaving the work site. Change clothing before leaving workplace and wash before reuse. Do not eat, drink, or smoke while using product.

Hand protection:

Suitable impervious protective gloves (latex, nitrile, etc.). Breakthrough time is not tested for this product. Change gloves often if possible.

Respiratory protection:

A NIOSH-approved respirator with filter for organic vapours is recommended where local ventilation is not adequate.

Eye/Face protection:

Protective goggles/safety glasses.



Safety Data Sheet

BS-3360

Wood & Parquet Adhesive

Issued date: 08/05/17

Revision date: -

Revision No.: 0

9. Physical and chemical properties

Appearance	:Viscous liquid
Odour	:Mild odour
Odour threshold	: Not determined
рН	:4-6
Freezing/Melting point	: Not determined
Boiling point range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability	: Not classified as flammable
Explosive properties	: Not classified as explosive
Oxidising properties	: Not classified as oxidising
Vapour pressure	: Not applicable
Vapour density	: Not applicable
Relative density	: 1.20 - 1.22
Solubility in water	: Soluble in water
N-octanol/water	
partition coefficient	: Not determined
Decomposition temperature	: Not determined
Viscosity	: Not determined

10. Stability and reactivity

Reactivity:

No reactive hazards known.

Stability:

Stable under recommended handling and storage conditions.

Conditions to avoid:

None known.

Hazardous reactions:

During normal storage, hazardous decomposition will not occur. At higher temperatures, decomposition productsdepend on the temperature, air supply and presence of other materials. Irritant gas and vapours will be produced.

Hazardous decomposition products:

None known.

Incompatible materials:

Strong oxidising agents.

11. Toxicology information

No specific oral, inhalation or dermal toxicology data is known for this product. Any toxicological data included in this section is based on the data associated with the components.

Acute oral toxicity, LD₅₀ (rat):

Not classified based on available information and/or concentration of components.



Safety Data Sheet

BS-3360

Wood & Parquet Adhesive

Issued date: 08/05/17 Rev	rision date: - Revision N	lo.: 0
Limestone	>2,000 mg/kg	
Methanol	5,629 mg/kg	

Acute dermal toxicity, LD₅₀ (rabbit):

Not classified based on available information and/or concentration of components.

Methanol	17,100 mg/kg

Acute inhalation toxicity, LC₅₀ (6 hours, rat):

Not classified based on available information and/or concentration of components.

Methanol	43.68 mg/L
	Ũ

Serious eye damage/eye irritation:

Not classified based on available information and/or concentration of components.

Limestone	Not eye irritant.
Methanol	Not eye irritant.

Skin corrosion/skin irritation:

Not classified based on available information and/or concentration of components.

Limestone	Notskin irritant.
Methanol	Not skin irritant.

Respiratory/Skin sensitisation:

Not classified based on available information and/or concentration of components.

Limestone	Not sensitising on skin.
Methanol	Not sensitising on skin.

Germ cell mutagenicity:

Not classified based on available information and/or concentration of components.

Limestone	Negative genotoxicity in vitro.
	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .

Carcinogenicity:

Not classified based on available information and/or concentration of components.

Reproductive toxicity:

Not classified based on available information and/or concentration of components.

Specific target organ toxicity - single exposure:

Not classified based on available information and/or concentration of components.



Safety Data Sheet

BS-3360

Wood & Parquet Adhesive

Issued date: 08/05/17

Revision date: -

Revision No.: 0

Specific target organ toxicity - repeated exposure:

Not classified based on available information and/or concentration of components.

Limestone	Exposure for 6 weeks by ingestion on rats. NOAEL: 1,000 mg/kg
Methanol	Exposure by ingestion for 3 days on monkeys. LOAEL: 2,340 mg/kg bw/day.
	Exposure by inhalation for 13 weeks on rats. NOAEC: 1.06 mg/L

Aspiration toxicity:

Not classified based on available information and/or concentration of components.

Likely route of administration:

Skin contact and ingestion.

12. Ecological information

Individual components of this mixture have been independently tested by the raw material suppliers and any known results have been presented below. The results for the individual components may not be representative of the ecological toxicity of this finished product. This finished product has not been tested to determine individual toxicological/ecological limits.

Ecology toxicity:

No adverse effect on aquatic organisms is predictedbased on available information and/or concentration of components.

Limestone Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC_{50} : >100 mg/L Exposure for 48 hours, EC_{50} : >100 mg/L Exposure for 72 hours, EC_{50} : >14 mg/L
Methanol Toxicity to fish Toxicity to crustacean	Exposure for 96 hours, LC ₅₀ : 12,700 mg/L Exposure for 96 hours, EC ₅₀ : 18,260 mg/L

Persistence and degradability:

Not likely to be persistentbased on available information and/or concentration of components.

Methanol	Readily biodegradable.
	Exposure for 20 days, 95% biodegradation.

Bioaccumulative potential:

No bioaccumulation potential based on available information and/or concentration of components.

Methanol	BCF: 0.2

Mobility in soil:

No data available.

13. Disposal information



Safety Data Sheet

BS-3360

Wood & Parquet Adhesive

Issued date: 08/05/17

Revision date: -

Revision No.: 0

Waste treatment/disposal methods - unused products

Waste disposal must be in compliance with environmental protection requirements and local regulations.

Waste treatment/disposal methods - contaminated packaging

Dispose of as unused product. Empty container should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Road transport (UNRTDG)	: Not regulated as dangerous goods.
UN number	:Not applicable
Proper shipping name	:Not applicable
Technical name	:Not applicable
Hazard class	:Not applicable
Classification code	:Not applicable
Packing group	:Not applicable
Marine transport (IMDG) UN number Proper shipping name Technical name Hazard class EmS Packing group Marine pollutant	: Not regulated as dangerous goods. :Not applicable :Not applicable :Not applicable :Not applicable : Not applicable :Not applicable : Not applicable : Not applicable
<u>Air transport (IATA)</u>	: Not regulated as dangerous goods.
UN number	:Not applicable
Proper shipping name	:Not applicable
Technical name	:Not applicable
Hazard class	:Not applicable
Packing group	:Not applicable

15. Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical in question:

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2010 (Malaysia)

Occupational Safety and Health (Classification, Labelling, and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 (Malaysia)

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (European Union)

Occupational Safety and Health Administration (OSHA) (2006) Air Contaminants. 29 CFR 1910.1000 (United States of America)

Work Health and Safety Act 2011 (Australia)

EH40/2005 Workplace exposure limits (United Kingdom)

Chemical inventory status:

Canada DSL/NDSL : All ingredients listed or exempt. China IECSC : All ingredients listed or exempt.

Safety Data Sheet

BS-3360

Wood & Parquet Adhesive

Issued date: 08/05/17

Bossi

Revision date: -

Revision No.: 0

Japan ENCS	: All ingredients listed or exempt.
Korea KECI	:All ingredients listed or exempt.
Philippines PICCS	:All ingredients listed or exempt.
United States TCSA	:All ingredients listed or exempt.

16. Other information

Definitions:

: Time-weighted average.
: Short-term exposure level.
: Occupational Safe and Health Act
: Workplace exposure limits
: The minimum dose required for lethal effects in 50% of agiven population of test specimens.
: part per million
: body weight
: National Institute for Occupational Safety and Health.
: United Nations Recommendations on the Transport of Dangerous Goods
: International Maritime Dangerous Goods
: International Air Transport Association
: Australian Inventory of Chemical Substances
: Domestic Substance List
: Non-domestic Substances List
: Inventory of Existing Chemical Substances in China.
:Existing and New Chemical Substances.
: Korea Existing Chemicals Inventory.
: Philippines Inventory of Chemicals and Chemical Substances.
: Toxic Substances Control Act.

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist. The details contained herein are based on our present state of knowledge and experience incharacterising our product with regard to any possible safety requirement at the date of its publication. We do, however, pass them on without any warranty or property assurances.