



Technical Data Sheet

BS-8580 Paint Remover



Features

- ◆ Non-Caustic
- ◆ Cost Effective
- ◆ Super Strong and Fast Reacting
- ◆ High Viscosity
- ◆ Works on Vertical Surfaces

Packaging

- ◆ 500 ml (tin)~24/carton
- ◆ 1.0 L (tin)~12/ carton
- ◆ 3.5 L (tin)~6/carton

Storage

- ◆ Store in a dry and cool place with temperature below 30 °C
- ◆ Use within 12 months from date of production

Product Specification

Principal Composition	: Blend of highly reactive solvent
Viscosity	: 1,200 cPs
Specific Gravity	: 1.2 ± 0.1

Description

A Paint Remover penetrates into successive coats of paint, varnish or enamel. It is super strong and fast reacting yet non caustic hence will not damage bared surfaces. It is highly viscous and can be applied on vertical surfaces.

Applications

Removal of coatings from metal, wood, plaster and glass. Removal of enamel paints, varnishes and bitumens. Can also soften acrylic paints and glues.

Directions

1. Warning: Product may splash out when removing inner cap.
2. Apply a thick coat onto the painted surfaces with a brush.
3. Leave it for 10 minutes to react with the paint.
4. Remove the softened paint with a paint stripper.
5. Close cap after use and store in cool, dry place.

Caution

Flammable liquid and vapour. Harmful if swallowed. Suspected of causing cancer. May cause damage to organs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof equipment. Do not breathe fume. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF exposed or concerned: Call a POISON CENTER or doctor. Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.