

Technical Data Sheet

BS-2670 Coldroom Mastic



Features

- ◆ Moisture Resistant
- ◆ Non-Skinning
- ◆ Excellent Adhesion

Available Colors

- ◆ White

Packaging

- ◆ 300 ml~24/carton

Storage

- ◆ Store in a dry and cool place, below 30 °C.
- ◆ Use with 24 months from date of production.

Product Specification

Appearance	: Non-Sagging Paste
Odour	: Mild Mineral Oils
Density	: 1.55 – 1.65 gm/ml
Slump	: 2.5 mm (Maximum)
Shrinkage	: 5 % (Maximum)
Service Temperature	: -40 °C to 80 °C

Description

A one-component, non-drying, polybutene based mastic that does not harden but remains permanently soft. It has excellent resistance to water vapor transmission.

Applications

Well-suited for sealing cold room and other pre-fabricated construction applications. Ideal for sealing most plastics, metals, glass, masonry, and wood.

Directions

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Surfaces should be cleaned with alcohol, M.E.K. or other suitable solvent. Do not use soap or detergent.
3. For a neat finish, apply masking tape and remove it before sealant skins over.
4. Cut nozzle at 45° angle to desired bead-width and apply to substrate with cartridge gun.
5. Uncured sealant can be cleaned up with mineral spirits.

Directions

Not recommended for following applications:

- ◆ Apply in exposed joints where there is dirt pick-up or hand contact.
- ◆ Used in areas subject to dynamic stress.
- ◆ Mobile homes, truck bodies.

Caution

May cause damage to central nervous system through prolonged or repeated exposure by inhalation. Do not breathe vapours. Get medical advice/attention if you feel unwell. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.