

	<b>BOSSIL TECHNOLOGY SDN. BHD.</b>	Issue Date.: 26/02/19
	Technical Data Sheet	Revision No.: 0
	<b>BS-3360150</b> Wood & Parquet Adhesive	Revised Date: - Page: 1 Of 1

### **Product Specification:**

Appearance	White viscous liquid
Density	1.21 – 1.23 g/mL
Viscosity at 25°C (Brookfield HA 6, 10 rpm)	20,000 – 30,000 cps
Solid	39 – 41%
Shelf Life	12 months
Content	150 g bottle



### **Product Description:**

A water-based adhesive that is excellent for wood bonding application. It features quick setting, superior bonding strength and it bonds variety of porous substrates.

### **Applications:**

Ideal for parquet installation and repair, wood joining, PVC lamination, furniture repair, wooden frames, woodworking projects, etc. **NOTE:** not for outdoor use

### **Directions:**

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Apply the adhesive to both surfaces if the material is absorbent. Press together firmly and leave to dry.
3. Replace cap after use and store in a cool and dry place.

### **Caution:**

Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

### **Storage:**

Store in dry and cool place with temperature below +30°C.  
Use within 12 months from date of production.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of various of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

**- END**

-