Bossil	BOSSIL TECHNOLOGY SDN. BHD.	Issue Date.:	26/02/19
	Technical Data Sheet	Revision No.:	0
	BS-8122 Craft Glue	Revised Date:	-
		Page:	1 Of 1

Product Specification:

Appearance Specific Gravity Viscosity at 25°C (Brookfield LV 4, 10 rpm) Solid Shelf Life Content White viscous liquid (Dries clear) 1.05 ± 0.03

20,000 – 30,000 cps 36 – 40% 12 months 125 g bottle



Product Description:

A multi-purpose PVA adhesive formulated for household repairs and crafts. It is ideal for porous materials such as wood, papers, cards, fabrics, leather, plaster, polystyrene and much more.

Applications:

Ideal for usage of school craft, DIY, wood and furniture repair, PVC lamination, book binding, polystyrene, etc.

Directions:

- 1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
- 2. Apply the adhesive to both surfaces if the material is absorbent. Press together firmly and leave to dry.
- 3. Replace cap after use and store in a cool and dry place.

Caution:

Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Storage:

Store in dry and cool place with temperature below +30°C. Use within 12 months from date of production.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of various of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

