

**BS-523 SPRAYABLE CONTACT ADHESIVE** 

**Page:** 1

Compilation date: 26/07/2018

Revision No: 0

## Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## Product name: BS-523 SPRAYABLE CONTACT ADHESIVE

Product code: VT-322

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company name:	Bossil technology Sdn. Bhd.
	22A-1, Jalan Tasik Utama 10,
	The Trillium @ Lake Fields,
	Sg. Besi,
	Kuala Lumpur,
	57000
	Malaysia.
Tel:	+6016-2119190
Email:	sales@bossil.com

## 1.4. Emergency telephone number

# Section 2: Hazards identification

2.1. Classification of the substa	2.1. Classification of the substance or mixture		
Classification under CLP:	STOT RE 2: H373; Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Repr. 2: H361f; Skin Irrit.		
	2: H315; STOT SE 3: H336		
Most important adverse effects:	Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or		
	dizziness. Suspected of damaging fertility. May cause damage to organs through		
	prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.		

## 2.2. Label elements

Label elements:	
Hazard statements:	H225: Highly flammable liquid and vapour.
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H361f: Suspected of damaging fertility.
	H373: May cause damage to organs through prolonged or repeated exposure.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark

## **BS-523 SPRAYABLE CONTACT ADHESIVE**

**Page:** 2



**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

### TOLUENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-625-9	108-88-3	-	Flam. Liq. 2: H225; Repr. 2: H361d;	30-50%
			Asp. Tox. 1: H304; STOT RE 2: H373;	
			Skin Irrit. 2: H315; STOT SE 3: H336	

## N-HEXANE

203-777-6	110-54-3	-	Flam. Liq. 2: H225; Repr. 2: H361f;	10-30%
			Asp. Tox. 1: H304; STOT RE 2: H373;	
			Skin Irrit. 2: H315; STOT SE 3: H336;	
			Aquatic Chronic 2: H411	

LOW BOILING POINT NAPHTHA - SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH.

265-192-2	64742-89-8	-	Asp. Tox. 1: H304; Flam. Liq. 1: H224;	10-30%
			Skin Irrit. 2: H315; Aquatic Chronic 2:	
			H411	

## Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

## BS-523 SPRAYABLE CONTACT ADHESIVE

Page: 3

Ingestion: Wash out mouth with water. Consult a doctor. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor. 4.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. The eyes may water profusely. Ingestion: There may be soreness and redness of the mouth and throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 4.3. Indication of any immediate medical attention and special treatment needed **Immediate / special treatment:** Eye bathing equipment should be available on the premises. Section 5: Fire-fighting measures 5.1. Extinguishing media **Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. 5.2. Special hazards arising from the substance or mixture Exposure hazards: In combustion emits toxic fumes. 5.3. Advice for fire-fighters Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Section 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. 6.2. Environmental precautions Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## BS-523 SPRAYABLE CONTACT ADHESIVE

Page: 4

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

8.1. Control parameters

#### Hazardous ingredients:

## TOLUENE

#### Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m3	384 mg/m3	-	-

**Respirable dust** 

## N-HEXANE

UK 72 mg/m3
-------------

**DNEL/PNEC Values** 

DNEL / PNEC No data available.

8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State:	Liquid
Colour:	Light yellow
Odour:	Characteristic odour
Evaporation rate:	Not applicable.
Oxidising:	Not classified as oxidising

Solubility in water: Not determined

#### **BS-523 SPRAYABLE CONTACT ADHESIVE**

# Viscosity:400-500cPsBoiling point/range°C:No data available.Flammability limits %: lower:No data available.Flash point°C:<23</td>Part.coeff. n-octanol/water:No data available.Autoflammability°C:No data available.Relative density:0.83VOC g/I:No data available.

9.2. Other information

Other information: No data available.

#### Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

#### Section 11: Toxicological information

11.1. Information on toxicological effects

#### Hazardous ingredients:

#### TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

## BS-523 SPRAYABLE CONTACT ADHESIVE

#### **Page:** 6

#### N-HEXANE

IPR	RAT	LDLO	9100	mg/kg
IVN	MUS	LDLO	831	mg/kg
ORL	RAT	LD50	25	gm/kg

### **Relevant hazards for product:**

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Reproductive toxicity		Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### Section 13: Disposal considerations

# BS-523 SPRAYABLE CONTACT ADHESIVE

	Page:
13.1. Waste treatment methods	
Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.
ection 14: Transport informati	on
14.1. UN number	
UN number:	UN1133
14.2. UN proper shipping name	
14.3. Transport hazard class(es)	
Transport class:	3
14.4. Packing group	
Packing group:	II
14.5. Environmental hazards	
Environmentally hazardous:	Yes Marine pollutant: No
14.6. Special precautions for us	er
Special precautions:	No special precautions.
Tunnel code:	D/E
Transport category:	2
Section 15: Regulatory informat	tion
15.1. Safety, health and environ	mental regulations/legislation specific for the substance or mixture
Specific regulations:	Not applicable.
15.2. Chemical Safety Assessme	ent
Chemical safety assessment:	A chemical safety assessment has not been carried out for the substance or the mixture
	by the supplier.
Section 16: Other information	
Other information	
Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H224: Extremely flammable liquid and vapour.
	H225: Highly flammable liquid and vapour.

## **BS-523 SPRAYABLE CONTACT ADHESIVE**

H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H361d: Suspected of damaging the unborn child.
H361f: Suspected of damaging fertility.
H373: May cause damage to organs through prolonged or repeated exposure.
H411: Toxic to aquatic life with long lasting effects.
Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Page: 8